



Recommended PCB LAYOUT
TOL.:±0.05

Physical:

Housing: Thermoplastic UL 94V-0

Contact: Selective Gold Flash

Specifications:

Voltage Current rating: 1A. 50V AC

Insulation Resistance: 1000Mohm Min

Contact Withstanding Voltage:

AC 500V For 1 Minute

Temperteure Rating: -40° To +85°

Part number:
XNT-MSC-801-08140

- 140: H=1.40mm
- 200: H=2.00mm
- 250: H=2.50mm
- 300: H=3.00mm
- 350: H=3.50mm
- 425: H=4.25mm
- 470: H=4.70mm

		深圳市鑫南天科技有限公司 Shenzhen XinNanTian Technology Co., Ltd			
		DIMENSIONS INIT: mm UNLESS OTHERWISE SPECIFIABLE	PRODUCT NAME : mini Smart card connector	DRAWING: COCO	DATE: 2014/01/15
DIMENSION TOLERANCE X.X: ± 0.38 X.XX: ± 0.25 X.XXX: ± 0.10 ANGULAR: ± 1°	PRODUCT NO. : XNT-MSC-801-08140	CHECK: AG	DATE: 2014/01/15		
	DRAWING NO. : XNT-MSC-801-08140	APPROVED: JEFF	DATE: 2014/01/15		
		SCALE: NA	DWG' ID: P D	REV.: A	
				PAGE: 1 OF 1	

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				
3				