


PIN NO.	PIN NAME
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O



MATERIAL:

Insulator: High Temperature Thermoplastic, UL 94V-0.

Contact: Copper Alloy

SHELL: SUS

PLATING:

Contact: Plated 50u'' Ni Overall Contact Au 1u, Pad Au 0.8u

Shell: clean

Electrical:

Current Rating :0.5Amps max

Voltage Rating :5V AC/DC

Ambient Temperature Range : -40°C ~ $+85^{\circ}\text{C}$


Storage Temperature Range : -40°C to $+85^{\circ}\text{C}$

Ambient Humidity Range : 95% R. H. Max.

Contact Resistance: 80mΩ max.

Insulation Resistance: 100M Ω min./100V DC

Mating cycles:5,000 insertions



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ± 0.05

						深圳市鑫南天科技有限公司 Shen zhen Xin Nan Tian Technology Co., Ltd					
DIMENSIONS INT.: ■ UNLESS OTHERWISE SPECIFIABLE DIMENSION TOLERANCE I.X. ± 0.15 I.IX. ± 0.10 I.TIX. ± 0.05 ANGULAR: ± 1°											
PRODUCT NAME:						MICRO-SIM 封装式1.50H 6P					
PRODUCT NO.:						788000-001					
DRAWING NO.:						XNT-049					
											
SCALE:						DATE:					
1:1						COCO					
TWE ID:						JANY					
c d						APPROVED:					
A						JTEF					
EOL :						DATE:					
1 or 1						2022/12/29					
2022/12/29						2022/12/29					